

# Product Data Sheet

## Protection Mat Strips SM-R



Easy to handle protection mat strips made of polyester fibers for use at upstands at roof perimeter areas and penetrations, particularly in combination with Fixodrain® XD 20.

### Technical Data

EDP No. 2035

#### Protection Mat Strips SM-R

Mat strips made of non-rotting polyester fibers.

Color:	grey	
Thickness:	ca. 0.12 in.	(ca. 3 mm)
Weight:	ca. 0.07 lbs/sq. ft.	(ca. 320 g/m <sup>2</sup> )
Water retention capacity:	ca. 0.07 gal/sq. ft.	(ca. 3 l/m <sup>2</sup> )
Strength class:	3	
Building material class:	B2	
Melting point:	ca. 500° F	(ca. 260 °C)
Dimensions:		
EDP No. 2035		
rolls, ca. 135 sq. ft. (12.5 m <sup>2</sup> )	ca. 1.6 ft. x 82.0 ft.	(ca. 0.50 m x 25.00 m)

### Features

- resistant to mechanical strain
- high quality protection layer
- the rear side is sprayed with pressure-sensitive adhesive
- easy to handle
- bitumen and polystyrene compatible
- heat resistant
- biologically neutral
- non-rotting
- made of recycled fibers

### Installation Instructions

Install the Protection Mat Strips SM-R above a water-proofing or root barrier. If used as fitting piece along edges or penetrations consider an overlap of 4 inch. The protection mat has to be taken above

the Growing Media along edges and at roof penetrations. Cut the protection mat in situ at roof penetrations. Consider an allowance for overlap and wastage of ca. 5–15 %.

### Health and Safety

This product does not require a material safety data sheet (MSDS) according to the OSHA Hazard Communication Standard (29 CFR 1910.1200). When used as recommended or under ordinary

conditions, it should not present a health and safety hazard. However, an MSDS can be provided as a courtesy in response to a customer request.