# Subject to technical alterations and printing errors • First edition 09/2016; Revised 11/2017

# Product Data Sheet Inspection Chamber KS 10







EDP No. 4010



Inspection chambers for protection and inspection of roof outlets for extensive green roofs and gravel roofs, with extension pieces also suitable for intensive green roofs.




### Technical Data

## Inspection Chamber KS 10

Made of plastic-coated aluminum with lateral slots for water passage. Detachable cover made of galvanized, plastic-coated steel with two finger holes.

Color:	old silver-antique		
Height:	ca. 3.9 in.	(ca. 100 mm)	(H)
Outer dimension of the Chamber:	ca. 11.8 x 11.8 in.	(ca. 300 x 300 mm)	(0)
(at transportation)			
Flange:	ca. 11.8 x 20.9 in.	(ca. 300 x 530 mm)	(F)
(extended, including chamber)			
Aperture dimension:	ca. 9.4 x 9.4 in.	(ca. 240 x 240 mm)	(A)
Slot width:	ca. 0.1 in.	(ca. 3 mm)	
Weight:	ca 6.2 lbs	(ca. 2.8 ka)	



### Accessories:

Extension Piece KSA 8 EDP No. 4008 Extension Piece KSA 20 EDP No. 4020

for elevation of KS 10 in segments of ca. 3.1 in. (ca. 80 mm) or ca. 7.9 in. (ca. 200 mm).

### **Features**

- low transport volume, yet fix positioning achieved by superimposed load when installed
- fits all outlets, d < 10 in.
- corrosion-resistant
- fine lateral slots allow for an installation in bulk material
- elevation with additional extension pieces

### **Installation Instructions**

Cut holes into all layers of the build-up in the size of the drain. Then install the Inspection Chamber KS10 on top of the drainage element above the drain. Install the filter sheet by rolling it over the inspection chamber and cutting it, ensuring that all slots of the inspection chamber remain uncovered, but the flanges remain covered.

# **Health and Safety**

This product does not require a material safety data sheet (MSDS) according to the OSHA Hazard Communication Standard (29 CFR 1910.1200). When used as recommended or under ordinary

conditions, it should not present a health and safety hazard. However, an MSDS can be provided as a courtesy in response to a customer request.

